

An Australian Government Initiative


Groundwater Education Investment Fund Project

Borehole Infrastructure Report

Borehole Type	Multi-Level Piezometer	GPS Easting	(MGA-94	369046		
Unique Well ID	18137	GPS Northing	Zone 53)	7526600		
Completion Date	29 November 2011	Location		Pine Hill Station, NT		
Drilled By	NRETAS	Installed By		NRETAS		
Monument Type	Round-White-Swing Top	Depth Drilled		66.0 m		
Monument Diameter/Width	216 mm	Drilled Diameter/Method		200 mm (min), Rotary Air		
Development Details		Airlif	t 7 L/s.			

Project Comments: 18137 is a triple completion multi-level piezometer. It is located adjacent to 18138. Together, these bores provide a nest of five piezometers sampling different depths in the unconfined aquifer.

Bore ID	Casing Size (mm)/ Type	TOC (mAHD)	Casing Depth (mBGL)		Screen Size (mm)/ Aperture (mm)/ Type	Cement (mBGL)		Screen Depth (mBGL)		SWL (mTOC)	
	200/Steel		-0.8	5.7	NA	0.0	5.7	NA	NA	NA	
18137-3	50/PVC9	550.272	-0.725	39.6	50/1/PVC			37.6	38.6	14.355	
18137-2	50/PVC9	550.288	-0.755	47.1	50/1/PVC			45.1	46.1	14.381	
18137-1	50/PVC9	550.231	-0.725	52.5	50/1/PVC			50.5	51.5	14.337	





Map of Ti Tree Super Science Piezometer Locations, Pine Hill Station, NT.

Note* Appendix includes Well Completion, Lithology and Geophysical Logs, Hydraulic Test and Chemical Analysis.


Infrastructure Report prepared by:	Contact Details:	Checked by: Prof Peter Cook
Shiller	Stephanie.villeneuve@flinders.edu.au Office: 08 8201 2724	Petr ah


Well Completion Log






Lithology Log






Geophysical Logs

The portable Mount Sopris logging system was used to collect geophysical data from bore 18137-1. The 2PGS probe was used to collect natural gamma measurements, and the 2PIA probe was used to measure conductivity/induced resistivity.




Pumping Test


A pumping test was performed on piezometer 18137-1 on 5/02/2012 by attaching a level logger to a submersible Grundfos MP1 pump, lowering the pump to a depth of 20 mTOC and using a flow rate of 7.8 L/min. The results of the test are presented below. The pump was not able to draw down the water level very much in this piezometer. The report author may be contacted for the full data set.



A pumping test was performed on piezometer 18137-2 on 5/02/2012 by attaching a level logger to a submersible Grundfos MP1 pump, lowering the pump to a depth of 20 mTOC and using a flow rate of 8.3 L/min. The results of the test are presented below. The pump was not able to draw down the water level very much in this piezometer. The report author may be contacted for the full data set.



A pumping test was performed on piezometer 18137-3 on 5/02/2012 by attaching a level logger to a submersible Grundfos MP1 pump, lowering the pump to a depth of 22 mTOC and using a flow rate of 8 L/min. The results of the test are presented below. The report author may be contacted for the full data set.



Chemical Analysis

Basic chemical analysis of the dissolved solutes and concentration of ions in the borehole was performed. The testing also included hydrogen ion activity (pH) and fluid electrical conductivity (EC). Data from the chemical analysis is shown below.

Well ID	Date	SWL	Field Parameters				Laboratory Analyses							
	Sampled	m	рН	EC	Temp	Alkalinity	Ca ²⁺	K+	Mg ²⁺	Na+	Si	CI-	NO ₃ -	SO ₄ ²⁻
		TOC		μS/cm	°C	mg/L CaCo ³	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L
18137-3	5/02/2012	14.36	7.36	963	30	230	29.1	17.4	20.3	111	37.8	59.7	73.3	73.15
18137-2	5/02/2012	14.38	7.3	993	30.1	233	35.7	19.2	22.6	107	36.8	82.3	77.6	65.85
18137-1	5/02/2012	14.34	7.1	1129	30.4	226	41.3	19	23.5	120	31.7	116	69.5	86.34